SeaRox® Tape ALU



SeaRox Tape ALU is a single-sided aluminium tape. The tape consists of an aluminium foil carrier with an acrylic dispersion adhesive that is lined with siliconised paper.

Application

For sealing joints between SeaRox ALU and ALU-G faced stone wool products and when terminating at a metal surface.
The surface must be dry and clean - free of dust, oil and grease.

Product properties

Product property	Performance	Norms
Thickness carrier	0.03 mm	
Thickness total (incl release liner)	0.120mm	
Looptack	20 N/25 mm	
Peel adhesion	14 N /25mm (60 mins)	
Tensile strength length	37 N/25 mm	
Elongation at break	5 %	
Operating temperatures	- 20°C to + 110°C	-
Application temperatures	-10 C to 40 °C (surface free from ice or moisture)	
Fire classification	Low flame spread properties	IMO 2010 FTP Code

Installation

The surface must be dry and clean - free of dust, oil, grease and other contaminants. Minimum working temperature is 5°C.
The user must evaluate product suitability for any application.

Storage

1 year shelf life whilst stored in ambient room temperatures. Keep out of direct sunlight.

0575 0097

As ROCKWOOL has no control over insulation design and workmanship, accessory materials or applications conditions, ROCKWOOL does not warranty the performance or result of any installation containing ROCKWOOL products. ROCKWOOL's overall liability and the remedies available are limited by the general terms and conditions of sale. This warranty in lieu of all other warranties and conditions expressed or implied, including the warranties of merchantability and fitness for a particular purpose. ROCKWOOL Technical Insulation reserves the right to make necessary product changes at any time. Technical specifications are thus stated subject to change.

ROCKWOOL® Technical Insulation, ROCKWOOL®, SeaRox® and ProRox® are registered trademarks of ROCKWOOL A/S and cannot be used without a prior written consent.