
Facade cladding.
Architect Guide.
Rockpanel™
MADE
FROM STONE.™



RELEASE THE NATURAL POWER OF **STONE TO ENRICH MODERN LIVING**

We have a clear goal.

We want to make stone come alive in all its facets. This is our mission, which represents a new chapter in the history of the Rockwool Group. Let's start it together!

We are a family.

At the ROCKWOOL Group, we are committed to enriching people's lives. Our range of products reflects the diversity of the world's needs, supporting you in enjoying the comforts of modern living while reducing your carbon footprint along the way.

ROCKWOOL

ROCKWOOL thermal insulation helps in providing a safe environment for your little ones.

Rockfon

Rockfon products don't just keep the sound where you want it, they help keep every word or note crisp and clean.

Rockpanel

Our innovative facade solutions give you the freedom to explore the boundaries of your wildest design dreams. So, if you can imagine it, you can build it.

Grodan

Our precision growing products increase the amount you can grow, improve the quality of what you grow, and limit your operating risks.





MADE




MADE
FROM




MADE
FROM
STONE



INDEX

About us. **3**

Advantages of Rockpanel. **13**

Sustainability. 16

Cradle To Cradle Certified®. 18

Design freedom. 20

Fire resilience. 28

Ease of use. 30

Durability. 32

Rockpanel Design overview. **35**

Design facades. **36**

Rockpanel COLOURS. 38

Rockpanel CHAMELEON. 46

Rockpanel METALS. 52

Rockpanel Nature Facades. **58**

Rockpanel WOODS. 60

Rockpanel STONES. 66

Rockpanel PREMIUM. **72**

Rockpanel Accessories. **80**

Technical guide **88**



IT COMES FROM **WITHIN.**


Stone has an inner quality that shows all the way through. A feel to the touch and a certain liveliness, that leaves most manmade materials feeling rather numb in comparison. This inner quality of stone is only surpassed by its inherent qualities as facade cladding.

A sustainable choice that is naturally fire resilient and both functionally and aesthetically durable. Rock-solid yet featherlight, Rockpanel can be sawn, bent, and shaped to fit any design. We offer the aesthetics of natural materials, indefinite patterns, and various surfaces.

And this is only the beginning. As our facade cladding is made from volcanic basalt - an abundant resource, they themselves become a resource when recycled into new stone wool products - many years from now.







NATURALLY INHERENT
QUALITIES DERIVED FROM STONE.

Rockpanel is recognised for its blend of natural qualities that make it a unique choice for exterior cladding and other architectural applications. Derived from the abundantly available rock, basalt, Rockpanel possess inherent natural properties that contribute to their durability, sustainability, fire resilience, ease of installation and aesthetic verstaility.

Sustainability

Rockpanel is made from the natural abundant resource and recycled materials and is endlessly recyclable. As documented in ETA, the intended working life is 50 years.

Design freedom

With more than 200 colours and designs available, plus the option to customize, Rockpanel offers design freedom with the option to bend and curve.

Fire resilience

Rockpanel can withstand extremely high temperatures as it has a very low calorific content. Most Rockpanel boards are classified as Euroclass A2-s1,d0, contains hardly any combustible materials and is free of fire-retardants additives.

Ease of use

Rockpanel is light-weight, can be cut with standard woodworking tools and no edge treatment is needed. Rockpanel is also dimensionally stable.

Durability

The aesthetic and functional durability of facade cladding is crucial to its longevity. Dimensional stability, resistance to weathering and no rot, and no fungus, are crucial. This is at the core of Rockpanel. The intended working life of Rockpanel boards is 50 years (ETA).


SUSTAINABILITY.

TO US, SUSTAINABILITY IS **MORE THAN JUST A BEAUTIFUL FACADE.**

It is our inner nature. And it goes all the way through as Rockpanel is part of the ROCKWOOL Group.

Basalt, the raw material in Rockpanel is an abundant resource, as the Earth produces more than we can use. And we can produce more than 400 m^2 facade cladding from only 1 m^3 of basalt. Our basalt stone is furthermore sourced close to our ROCKWOOL factory with a clear code of conduct for supply and mining.

Additionally, Rockpanel facade cladding is also made of up to 50% recycled materials, that would otherwise end up in landfill. And this is only the beginning. Easy to dismantle, Rockpanel facade cladding can re-enter the production process again and again to become new stone wool products, while we're still able to guarantee the same level of high-quality.

Our recycling, Rockcycle® programme has run for more than 25 years, constantly reducing the amount of waste going to landfills, as well as the use of virgin raw materials.

Working with Rockpanel is more than working with the inherent natural qualities of stone. It is also working with all the documentary tools that provide ease of mind. We offer an EPD (Environmental Product Declaration) for all our products, providing insights about the environmental impact of each stage of the product life cycle.



CONTRIBUTING TO CIRCULAR ECONOMY **WITH CRADLE TO CRADLE CERTIFIED® PRODUCTS.**

98% of the Rockpanel portfolio is Cradle to Cradle certified level silver in accordance with the rigid product standard version 4.0 which is the most ambitious and actionable global standard yet for developing products that are safe, circular and responsibly made.


Cradle to Cradle Certified® is a globally recognised standard which credits solutions that support the circular economy and make a positive impact on both people and the planet.

This certification further represents yet another initiative consolidating our position as a responsible manufacturer.

Being Cradle to Cradle Certified is also recognised by several major building rating schemes such as e.g. LEED, and DGNB. Therefore, when using a Cradle to Cradle Certified product, you can earn more points in these building rating schemes.



C2CCERTIFIED.ORG



WHAT IS
CRADLE TO CRADLE CERTIFIED?

Cradle to Cradle Certified® is the world's most advanced, science-based standard for designing and making products today that enable a healthy, equitable, and sustainable tomorrow.

It is a holistic standard that verifies a product's performance across five critical areas of sustainability including: Material Health, Product Circularity, Clean Air and Climate Protection, Water and Soil Stewardship, and Social Fairness.

When a product is Cradle to Cradle Certified® it is internationally recognised as a safer, more sustainable product that supports the circular economy.


To learn more about our detailed score for each category, please see the graphic below or visit www.rockpanel.com/sustainability:

full scope
CERTIFIED
cradle to cradle
silver version 4.0
C2CCERTIFIED.ORG

Rockpanel Façade Cladding Silver
ROCKWOOL B.V. / Rockpanel

Version 4.0 / Renewal 23 May 2027 / Recertification every 3 years

	BRONZE	SILVER	GOLD	PLATINUM
MATERIAL HEALTH		●		
PRODUCT CIRCULARITY		●		
CLEAN AIR & CLIMATE PROTECTION		●		
WATER & SOIL STEWARDSHIP		●		
SOCIAL FAIRNESS		●		


DESIGN
FREEDOM.

IF YOU CAN ENVISION IT,
WE CAN MAKE IT COME TRUE.

Despite all its rock-solid qualities, Rockpanel also offers unparalleled design flexibility. And we use the term "unparalleled" quite literally here. For more than 30 years, we've been working with conscious architects and contractors to make inspiration come true.


Today, we produce stone wool cladding that not only looks and feels beautiful, but can also be sawn, bent, and shaped to fit practically any form or design vision. Curved or straight, we can make them with indefinite patterns, various surfaces and finishes in matte or gloss.

From smooth as polished granite to rough as a volcanic landscape. You can set your imagination free with Rockpanel Woods, Stones, Metals and other unique designs.

Just as you can choose from more than 200+ colours including the one, you can't find anywhere else.

Whether your architecture vision is elementary, irregular, symmetrical, curvilinear or adopts a squared, pyramid or triangular form, with Rockpanel you can define your project's unique identity.







ROUTING AND **PERFORATION.**

Enhance the depth and character of your facade design through engraving and perforation. These techniques allow you to create dynamic visual effects, transforming your facade into a striking architectural element.

Engraving adds a unique, personal touch, effectively conveying a message and allowing the facade to become a storytelling medium.

With Rockpanel, you benefit from inherent moisture resistance, eliminating the need for special post-treatment and ensuring lasting beauty and functionality.





BEND, SHAPE
AND CURVE.

In addition to colours and patterns, the design of the facade defines your building's character, influences its surroundings, and adheres to its function. With Rockpanel, you can enjoy maximum design freedom at lower costs.

Bend, shape, and curve your facade until a clear vision comes to life.

You design it; Rockpanel shapes it.











ENHANCE YOUR FACADE **WITH COLOUR.**

Transform your facade with a blend of vibrant colours, finishes, and designs. Choose from over 200+ RAL and NCS colours, or wood, stone, metals, and chameleon designs. Or create a bespoke design tailored to your design vision. Our customizable dimensions and flexible handling guarantee optimal efficiency and minimal cutting waste.

Matt, semi or high gloss? Pick the finish that best fits your design vision. Each level of reflection has its own character. And for an additional dimension, you can combine our different gloss grades for an even greater effect.

Please see page 77 to learn more.




THE EYE
IS IN THE DETAIL.



Details are important in order to implement an idea in the best possible way. By choosing the right corner profile you can increase the visual appeal of your facade. Elegant facades can also have sharp edges You can freely to choose your fixing method.


Fixing Rockpanel cladding is not just a technical requirement but also a design element.

Please refer to page 114 for more information on edge solutions.
















Rockpanel Headquaters, Roermond, The Netherlands



FIRE
RESILIENCE.



FIREPROOF
THE FUTURE.

Stone doesn't burn easily. An inherent quality, that makes our façade cladding inherently fire resilient without the need for adding any fire retardants. Volcanic basalt can withstand extremely high temperatures as it has a very low calorific content.

This amount of energy determines how much a certain material contributes to a fire. And this inherent fire resilience is now more vital than ever, as fires today develop 5 to 10 times faster than they did years ago.

Fire regulations differ from country to country, as do building habits.

Some countries have prescriptive measures in their building codes, while others have performance criteria. Across Europe, the Euroclass system classifies a products reaction to fire by classes A to F. A1 and A2 classifications for applications where high levels of fire resilience is needed such as residential buildings, hospitals, or schools - is desirable or even mandatory.

At the ROCKWOOL Group we believe fire resilience is always mandatory. So, to fireproof the future, we offer an extensive portfolio of Euroclass classified A2-s1,d0 facade cladding and A1 stone wool insulation.


EASE OF
USE.

EASY
DOES IT.

Imagine a façade cladding with all the aesthetics and sustainability qualities of stone. Combine it with the lightness and economy of manmade materials. Now, here comes the easy part.


Start installing it with no further preparation. As Rockpanel is insensitive to moisture and temperature changes, unlike timber, there is no further treatment needed to prevent mould, rotting or delamination.

Save time. Save working hours. Save money. Rockpanel arrives ready to be cut on site or offsite with normal woodworking tools to fit any design or application. And they are easy on the weight too. Whereas many manmade materials are heavy and might even require lifting equipment, Rockpanel is considerably lighter than most other facade cladding materials.

Whether your project is renovation or newbuild, Rockpanel offers the perfect balance between beauty and practicality – inspired by nature.




DURABILITY.




BEAUTIFUL
AND BUILT TO STAY THAT WAY.

Durability. The ability to endure almost anything is one of the most prominent qualities of Rockpanel. Our facade cladding is insensitive to moisture and humidity and is able to withstand extremely high temperatures, making it naturally fire resilient.


Any moisture absorbed is released directly without any change to the mechanical properties.


Furthermore, this unique durability is strengthened with literally no-maintenance, reducing cost of ownership, just as it can be graffiti-protected with a special coating.

Come rain, come snow, come sun, come wind, Rockpanel is inherently resistant to both moisture and UV-lighting – keeping the cladding's integrity.













ROCKPANEL DESIGN OVERVIEW

DESIGN **FACADES.**

Rockpanel **COLOURS.** **38 - 45**
Rockpanel **CHAMELEON.** **46 - 51**
Rockpanel **METALS.** **52 - 57**

NATURE **FACADES.**

Rockpanel **WOODS.** **60 - 65**
Rockpanel **STONES.** **66 - 71**

Rockpanel **PREMIUM.**

72 - 79

ACCESSORIES. **80**
TECHNICAL PROPERTIES. **85**
PRODUCT FEATURES OVERVIEW. **86 - 87**


DESIGN
FACADES.



LIMITLESS DESIGNS
AND THE ONE, THAT DOESN'T EXIST YET.

Be free to imagine with our design facades. From a vibrant but wide-ranging palette of colours –that are also ever changing, to a selection of industrial-looking hues, we have the design that makes your design dreams come true. Our three facade designs are Rockpanel Colours, Rockpanel Metals and Rockpanel Chameleon.



Rockpanel
COLOURS.











Rockpanel
COLOURS.

- Wide range of standard colours
- Option for custom colours
- Easy to clean
- Various colour systems available

The world is in colour.

Think of a yellow house. Or a pink one! Or a sober black with details in flaming red. Colours are not just a finishing touch to a facade. They can be the facade design itself. With Rockpanel Colours you have the freedom to experience architecture as a palette of possibilities –with over 200+ colours to choose from or the one you can't find anywhere else -Colour your imagination with Rockpanel Colours.

Key product properties

	Colours	**Unit**	**Test/classification method**
Thickness	8	mm	EN 325
Weight	9.4	kg/m²	
Reaction to fire*	A2-s1,d0		Euroclass EN 13501-1
Coating (optional)**	ProtectPlus		
Directionality	Non directional		
Standard gloss grade	Semi-gloss		
Gloss grades available**	Matt, high-gloss		
Colour stability (5000h) With ProtectPlus	3-4 or better 4 or better	Greyscale	ISO 105-A02

Standard board sizes



2500 x 1200 mm




3050 x 1200 mm

Additional width available: 1250 mm**
Custom length available: 1700-3050 mm**

*The Euroclass-classification of all Rockpanel products is based on testing with non-combustible mineral wool insulation. For the field of application covered by the classification, please see the relevant Declaration of Performance. For high-rise and high-risk buildings, Rockpanel recommends the application of non-combustible (Euroclass A1 or A2-s1, d0) cladding and insulation.

** Minimum order quantities apply, for more information contact Rockpanel.




RAL 7001


RAL 7012

RAL 9010


RAL 7031

RAL 080 80 05


RAL 7016


RAL 060 70 05


RAL 7021


RAL 7036


RAL 9011


RAL 7004


RAL 040 50 05

RAL9016


RAL 000 50 00*


RAL 060 50 05


RAL 7024


RAL 7037


RAL 080 30 05


RAL 5004**


RAL 9005


RAL 7022


RAL 8022

NCS S 0520-R10B*


RAL 3015*


RAL 010 30 44**


NCS S 0570-Y90R*


RAL 350 40 35**


RAL 030 50 50**


NCS S 4030-R50B*


RAL 3028*


RAL 4004*


RAL 3001*


RAL 4007*


RAL 3004


RAL 350 20 10**


RAL 010 20 20*


RAL 3007*


RAL 020 20 05*


NCS S 1080-Y50R**


RAL 2010

RAL 060 50 70

RAL 2012*

RAL 8023

RAL 040 50 70*

RAL 050 40 40*

RAL 3016

RAL 8024*

RAL 040 40 50

RAL 060 30 20*

RAL 3009

RAL 8028

RAL 050 30 10

RAL 060 70 20*

RAL 060 50 30*

RAL 8001*

RAL 100 90 20*

RAL 060 60 50**

RAL 100 90 50*

RAL 7006

NCS S 2050-Y*

RAL 070 70 60

RAL 1012*

RAL 070 60 75*

RAL 1032*

* Rockpanel Special
** Rockpanel Custom











The samples shown give a good impression of the actual design. However, it is not possible in print to accurately represent the true colours. Request free Rockpanel colour-/design-samples via www.rockpanel.com.





















Rockpanel
CHAMELEON.











Rockpanel
CHAMELEON.

- Chameleon effect
- Surface constantly changes
- Self-cleaning

Changing times - changing colour.

Only to Rockpanel. Rockpanel Chameleon is the facade, that will never be the same. Depending on the viewing angle or the sun's reflection, the facade will transform into a new vibrant colour due to a special crystal effect layer. The effect remains the same for decades -Dare to be extraordinary with Rockpanel Chameleon.

Key product properties

	Chameleon	Unit	Test/classification method
Thickness	8	mm	EN 325
Weight	9.4	kg/m²	
Reaction to fire*	A2-s1,d0		Euroclass EN 13501-1
Coating	ProtectPlus		
Directionality	Directional		
Standard gloss grade	High-gloss		
Gloss grades available**	Matt, semi-gloss		
Colour stability (5000h)	4 or better	Greyscale	ISO 105-A02

Standard board sizes



2500 x 1200 mm



3050 x 1200 mm

Custom length available: 1700-3050 mm**

*The Euroclass-classification of all Rockpanel products is based on testing with non-combustible mineral wool insulation. For the field of application covered by the classification, please see the relevant Declaration of Performance. For high-rise and high-risk buildings, Rockpanel recommends the application of non-combustible (Euroclass A1 or A2-s1, d0) cladding and insulation.

** Minimum order quantities apply, for more information contact Rockpanel.



Purple - Green - Blue



Red – Gold – Purple




Green – Brown

The samples shown give a good impression of the actual design. However, it is not possible in print to accurately represent the true colours. Request free Rockpanel colour-/design-samples via www.rockpanel.com.



















Rockpanel
METALS.














Rockpanel
METALS.

- Contemporary industrial design
- Self cleaning
- Elegant and refined look
- Low maintenance

Meet the metals. Made from stone.

Create industrial design facades with an ever-changing sheen from the light striking them. Rockpanel Metals consists of the main precious metals such as gold, silver, platinum aluminium, steel and copper. It also includes designs which will give any facade a distinctive patinated look. Thanks to an advanced technology, they have a beautiful worn finish, that will last for decades -Make your metal vision rock with Rockpanel Metals.

The **Elemental Metals** line consists of the main precious metals such as gold, silver, and platinum. It also includes other well-known metals such as aluminium, steel and copper.

The **Advanced Metals** line includes designs which will give any facade a distinctive patinated look. Thanks to an advanced technology, they have a beautiful worn finish, that will last for decades.

Key product properties

	Metals	**Unit**	**Test/classification method**
Thickness	8	mm	EN 325
Weight	9.4	kg/m²	
Reaction to fire*	A2-s1,d0		Euroclass EN 13501-1
Coating:	ProtectPlus		
Directionality Mostly Directional	Non directional designs: White Aluminium Grey Aluminium		
Standard gloss grades	Advanced metals, White aluminium & Grey aluminium: matt Other Elemental metals: semi gloss		
Gloss grades available**	Matt, semi-gloss, high-gloss		
Colour stability (5000h)	4 or better	Greyscale	ISO 105-A02

Standard board sizes



2500 x 1200 mm



3050 x 1200 mm

Additional width available: 1250 mm**
Custom length available: 1700-3050 mm**

*The Euroclass-classification of all Rockpanel products is based on testing with non-combustible mineral wool insulation. For the field of application covered by the classification, please see the relevant Declaration of Performance. For high-rise and high-risk buildings, Rockpanel recommends the application of non-combustible (Euroclass A1 or A2-s1, d0) cladding and insulation.

** Minimum order quantities apply, for more information contact Rockpanel. Availability depends on the specific design.

Elemental Metals


White Aluminium


Grey Aluminium


Steel


Gunmetal


Yellow Gold


Classic Gold


Silver


Platinum


Copper

Advanced Metals


Verdigris


Dark Copper


Bronze


Electrum


Brass


Titanium


Ultramarine


The samples shown give a good impression of the actual design. However, it is not possible in print to accurately represent the true colours. Request free Rockpanel colour-/design-samples via www.rockpanel.com.














NATURE
FACADES.

DESIGNED BY **NATURE.**

With our Rockpanel Nature facade designs, we don’t try to replicate nature, we salute it. Nature influences design, embodying a rich spectrum of warm shades and hues, and an intricate interplay with light and tactility. With our nature facade designs, we pay homage to these elements, saluting beauty and brilliance of the natural world.




Rockpanel
WOODS.













Rockpanel
WOODS.

- Authentic wood texture
- No visual repetition
- Wood that does not burn
- Low maintenance
- Colourfast

Textured Elegance. Naturally durable.

Our Rockpanel Woods collection captures the character of real, textured wood and expresses it in inherently durable, fire-resilient and low-maintenance stone. Now, you no longer have to choose between the look of wood and cladding performance – with Rockpanel Woods you get the best of both.

Rockpanel Woods cladding is available in 25 designs: 20 with highly wood-realistic textured surfaces, two with weathered surfaces, and three featuring a smooth, non-textured finish. The design freedom enabled by this wide range is complemented by the ease with which panels can be shaped and curved. Our customisation service lets you emulate existing facade claddings, making Rockpanel Woods ideal for remediation projects.

Key product properties

	Woods	**Unit**	**Test/classification method**
Thickness	8	mm	EN 325
Weight	9.4	kg/m²	
Reaction to fire*	A2-s1,d0		Euroclass EN 13501-1
Coating	ProtectPlus		
Directionality	Directional		
Standard gloss grade	Matt		
Gloss grades available**	Semi-Gloss, high-gloss		
Colour stability (5000h)	4 or better	Greyscale	ISO 105-A02

Standard board sizes



2500 x 1200 mm**



3050 x 1200 mm

Additional width available: 1250 mm**
Custom length available: 1700-3050 mm**

*The Euroclass-classification of all ROCKWOOL B.V. / Rockpanel products is based on testing with non-combustible mineral wool insulation. For the field of application covered by the classification, please see the relevant Declaration of Performance. For high-rise and high-risk buildings, Rockpanel recommends the application of non-combustible (Euroclass A1 or A2-s1, d0) cladding and insulation.

** Minimum order quantities apply, for more information contact Rockpanel.

Textured


Black Oak


Caramel Oak


Ceramic Oak


Marble Oak


Rhinestone Oak


Teak


European Beech


Canadian Maple


Monterey Pine


Aged Siberian Larch


Fraké Driftwood


Fraké Mauve


Fraké Amber


African Crimson Padouk


African Slate Padouk


Light Natural Bamboo


Rustic Brown Bamboo


Mocha Brown Bamboo


Deep Red Mahogany


Western Red Cedar


Weathered Missouri Oak


Weathered Barnwood Oak

Smooth


Alder


Cherry



Oak

The samples shown give a good impression of the actual design. However, it is not possible in print to accurately represent the true colours. Request free Rockpanel colour-/design-samples via www.rockpanel.com.





















Rockpanel
STONES.














Rockpanel
STONES.

- Light-weight
- Self-cleaning
- Low maintenance

It looks exactly what it is.

The beauty, feel, and strength of real stone. With Rockpanel Stones we offer both smooth and textured surfaces in a palette of natural colours such as chalk, limestone and choral. But in this case, it also comes with the flexibility and versatility in terms of freedom of design, fire resilience and ease of use. The feeling of rock-solid strength for generations to come. Built to last with Rockpanel Stones.

Textured Stones collection breathes new life into decorative cladding with its distinctive surface texture. With our 10 natural designs building projects incorporate this original stone texture blend organically with the surrounding environment.

Smooth Stones offers you the dream combination of a powerful, natural appearance with refined elegance. With 6 smooth designs, you can create a facade with a sleek, smooth finish with limitless possibilities to create visionary facades with an authentic look.

Key product properties

	Stones	**Unit**	**Test/classification method**
Thickness	8	mm	EN 325
Weight	9.4	kg/m²	
Reaction to fire*	A2-s1,d0		Euroclass EN 13501-1
Coating:	ProtectPlus		
Directionality	Directional		
Standard gloss grade	Matt		
Gloss grades available**	Semi-gloss, high-gloss		
Colour stability (5000h)	4 or better	Greyscale	ISO 105-A02

Standard board sizes

2500 x 1200 mm**

3050 x 1200 mm

Additional width available: 1250 mm**
Custom length available: 1700-3050 mm**

*The Euroclass-classification of all Rockpanel products is based on testing with non-combustible mineral wool insulation. For the field of application covered by the classification, please see the relevant Declaration of Performance. For high-rise and high-risk buildings, Rockpanel recommends the application of non-combustible (Euroclass A1 or A2-s1, d0) cladding and insulation.


** Minimum order quantities apply, for more information contact Rockpanel. Availability depends on the specific design.

Textured Stones

Carrara White


Claystone Grey


Amber Brown


Coral Red


Sapphire Blue


Moonstone Silver


Sandstone Ochre


Bronzite Brown


Quartz Grey


Tourmaline Black

Smooth Stones


Brownish Grey


Anthracite Green



Iron Grey


Ash Grey


Platinum Grey

Sandy Beige

The samples shown give a good impression of the actual design. However, it is not possible in print to accurately represent the true colours. Request free Rockpanel colour-/design-samples via www.rockpanel.com.



















Rockpanel
PREMIUM.



IMPRESSIVE FACADES.
UNIQUE AND INNOVATIVE

There are projects that we cannot imagine, because no one has imagined them yet. For those projects, we offer Rockpanel Premium, with unlimited design freedom. No matter how creative your design is, Rockpanel can help your design vision come true.


Rockpanel
PREMIUM.







Rockpanel
PREMIUM.

- Custom colours and designs
- Customised sizes
- Concealed fixing
- ProtectPlus as standard

Make your building unique.

Create unique designs with Rockpanel Premium. With design freedom you can combine all of our colours, designs and finishes, anyway you want it. Mix patterns from our other designs such as Rockpanel Woods or Rockpanel Stones with the uniqueness of Rockpanel Chameleon. And of course, any gloss grade is possible together with the option of concealed fixings.

Key product properties

	Premium	**Unit**	**Test/classification method**
Thickness	11	mm	EN 325
Weight	13.75	kg/m²	
Reaction to fire*	A2-s1,d0		Euroclass EN 13501-1
Coating	ProtectPlus		
Directionality	Depends on design		
Standard gloss grade	Depends on design		
Gloss grades available**	Matt Semi-gloss High-gloss		
Colour stability (5000h)	4 or better	Greyscale	ISO 105-A02

Standard board sizes



3050 x 1200 mm

Additional width available: 1250 mm***
Custom length available: 1700-3050 mm**

*The Euroclass-classification of all ROCKWOOL B.V. / Rockpanel products is based on testing with non-combustible mineral wool insulation. For the field of application covered by the classification, please see the relevant Declaration of Performance. For high-rise and high-risk buildings, Rockpanel recommends the application of non-combustible (Euroclass A1 or A2-s1, d0) cladding and insulation.

** Minimum order quantities apply, for more information contact your local sales representative. Availability depends on the specific design.

*** Not available for Chameleon.

Design without limits

Want to combine all of our colours, designs and finishes, anyway you want? Then Rockpanel Premium is right for you – with Custom colours and designs, and customised formats and dimensions.

Concealed fixing

With Rockpanel Premium we offer concealed fixing to create a seamless and aesthetically pleasing surface. Our concealed fixing system is not only a perfect solution from an aesthetic point of view, but also ensures a quick and easy installation and guarantees absolute stability.

Play with light

When realizing your project, you want every detail to be just right. That's why we offer three different gloss grades for almost all colours and designs: matt, semi-gloss and high-gloss. Pick the finish that best suits your design, or mix different gloss grades for an even greater effect.

ProtectPlus as standard

Facades face many challenges: sunlight, wind, dirt, and rain. Fortunately, Rockpanel Premium is designed to withstand even the harshest weather conditions. Thanks to their ProtectPlus coating, Rockpanel Premium offer excellent protection against external influences. They provide optimal colour retention and have enhanced self-cleaning properties, allowing rainwater to wash away most of the dirt. Additionally, graffiti can be easily removed with a special cleaning agent.

Perfection in all dimensions

To create the best looking result, Rockpanel
Premium offers even more flexibility in dimensions. The boards are available in any length you need between 1,700 mm and 3,050 mm. For a beautiful, cost-efficient and practically no-waste result. Rockpanel Premium is offered with 11 mm thickness.



Matt





Semi-gloss



Full gloss

The samples shown give a good impression of the actual design. However, it is not possible in print to accurately represent the true colours. Request free Rockpanel colour-/design-samples via www.rockpanel.com.















Rockpanel
ACCESSORIES.



Fasteners

Fixings for timber sub-construction

Fixing method	Suitable for Rockpanel
Ring shank nails (high performance) 35 mm	Colours / Metals / Chameleon / Woods / Stones
Torx screws 35 mm	Colours / Metals / Chameleon / Woods / Stones
Adhesive (consult the manufacturer of the adhesive system for detailed information)	Colours / Metals / Chameleon / Woods / Stones (only for Rockpanel A2 8 mm)

Fixings for aluminium sub-construction

Fixing method	Suitable for Rockpanel
Rivets SFS AP14-50180-S / AP14-50210-S	Colours / Metals / Chameleon / Woods / Stones / Premium
Rivets MBE FN-AL5-5x18 K14 / FN-AL5-5x21 K14	Colours / Metals / Chameleon / Woods / Stones / Premium
Screw SFS SDA4-D15-CS10/8-5.8x29-A4	Colours / Metals / Chameleon / Woods / Stones (only for Rockpanel A2 8 mm)
Adhesive (consult the manufacturer of the adhesive system for detailed information)	Colours / Metals / Chameleon / Woods / Stones (only for Rockpanel A2 8 mm)

Fixings for steel sub-construction

Fixing method	Suitable for Rockpanel
Rivets SFS SSO-D15-50180 / 50210	Colours / Metals / Chameleon / Woods / Stones / Premium
Rivets MBE FN-A4-5x18 K15 / FN-A4-5x21 K15	Colours / Metals / Chameleon / Woods / Stones / Premium
Self-drilling screws 25 mm JT6-FR-3 -5.5	Colours / Metals / Chameleon / Woods / Stones
Self-drilling screws 35 mm JT6-FR-3 -5.5	Colours / Metals / Chameleon / Woods / Stones

Concealed fixing

Only in combination with Rockpanel Premium A2 board in thickness 11 mm.

Systemcomponent
Blind fastener SFS TU-S-6x 11-A4 (for use with a 3mm panel clip)
Blind fastener SFS TU-S-6x 13-A4 (for use with a 5mm panel clip)
SFS HSS-Drill bit 6.0 x 43.5
SFS Depth locator for drill bit universal

PlankClip

Only in combination with Rockpanel A2 9mm.

Systemcomponent
SFS RCLIP (100x40x36)
SFS RCLIP-Short (60x42x36)
SFS Anchor TU-S (6x9mm)
SFS SDAW Fastener aluminium and timber
SFS Drill VHM 6.0 x 41.5
SFS Depth locator for HSS-drill
SFS PlankClip Starter-Kit





Other accessories



	Width	Quantity
EPDM Foamtape (adhesive)	36 mm	50 m[1]
EPDM Foamtape (adhesive)	60 mm	50 m[1]
EPDM Foamtape (adhesive)	80 mm	50 m[1]
EPDM Foamtape (adhesive)	100 mm	25 m[1]
EPDM Foamtape (adhesive)	130 mm	25 m[1]
Rockpanel Graffiti Cleaner		780 ml
Rockpanel Edge paint (only Rockpanel Standard Colours)		500 ml

Profiles for boards

High quality aluminium External Corner profiles, Edge profiles, Joint profiles and Starter profiles can be supplied in almost every RAL/NCS colour. Please contact Rockpanel for details of your local supplier.

Aluminium profiles – Rockpanel boards

	Standard length 3055 mm		Colours	Profile size*
	Profile A		Blanc anodised Standard Special/Custom	6, 8, 10 mm
	Profile B		Blanc anodised RAL 9005 / RAL 9010	One size fits all
	Profile C		Blanc anodised Standard Special/Custom	6, 8, 10 mm
	Profile D		Blanc anodised Standard Special/Custom	6, 8, 10 mm
	Profile E		Blanc anodised Standard Special/Custom	6, 8, 10 mm
	Profile F		Blanc anodised Standard Special/Custom	6, 8, 10 mm

	Standard length 3055 mm		Colours	Profile size*
	Profile G		Blanc anodised Standard Special/Custom	8 mm
	Profile H		Blanc anodised Standard Special/Custom	6, 8, 10 mm
	Profile I		Blanc anodised	One size fits all
	Profile J		Blanc anodised	One size fits all

Technical properties

Feature	Classification	Unit	Rockpanel A2 8 mm	Rockpanel A2 9 mm	Rockpanel A2 Premium 11 mm
Thickness	EN 325	mm	8	9	11
Fire classification	EN 13501-1		A2-s1,d0	A2-s1,d0	A2-s1,d0
Mechanical properties					
Modulus of elasticity m(E)	EN 310	N/mm^2	≥ 4015	≥ 4740	≥ 4740
Bending strength, length and width (f_{05})	EN 310 & EN 1058	N/mm^2	≥ 27	≥ 25.5	≥ 25.5
Physical properties					
Density, nominal	EN 323	kg/m^3	1170	1250	1250
Weight, nominal		kg/m^2	9.4	11.25	13.75
Thermal conductivity	EN 10456	W/(m·K)	0.47	0.55	0.55
Water vapour permeability (S_d) (at 23°C and 85% RH)	EN-ISO 12572 Rockpanel Colours	m	<1.7		
	Rockpanel with PP	m	<3.2		
Dimensional stabilty					
Cumulative dimensional change % (length)	EN 438-2	%	0.072	0.064	0.064
Cumulative dimensional change % (width)	EN 438-2	%	0.072	0.064	0.064

Feature	Classification	Subconstruction	Rockpanel A2 8 mm	Rockpanel A2 9 mm	Rockpanel A2 Premium 11 mm
Fixing types					
Screw 35 mm (Torx T20)	EN 10088	Timber	■		
Self-drilling screw 29 mm (Torx T25W)	EN ISO 3506	Aluminium	■		
Self-drilling screw 25 mm	EN ISO 3506	Steel	■		
Self-drilling screw 35 mm	EN ISO 3506	Steel	■		
Rivet	EN 10088	Aluminium, Steel	■		■
Adhesive fixing		Timber, Aluminium	■		
Plankclip fixing (SFS)		Timber, Aluminium		■	
Concealed fixing (SFS)		Aluminium			■

■ approved according to ETA

Product features overview

		Nature facades	
Feature	**Note**	**Rockpanel Woods**	**Rockpanel Stones**
APPLICATION			
High facades	Height > 18 m	■	■
Low facades	Height <10 m	■	■
Detailed solutions for roofs		■	■
AESTHETICS			
Type of cladding			
Board		■	■
Tongue and groove		–	–
Dimensions			
Standard dimensions (mm)	3050x1200	■	■
	2500x1200	□	□
Customised length (mm)	1700-3050	□	□
Special width (mm)	1250	□	□
Thickness (mm)		8 & 9	8 & 9
Surface			
Untreated		–	–
Primered only		–	–
Coloured surface		Woods look	Stones look
Custom colour		–	–
Customized design		O	O
Colour stability (5000 hours)	EN 105-A02	4 or better	4 or better
Standard gloss grades: Optional gloss grades:		Matt Semi-gloss, High-gloss	Matt Semi-gloss, High-gloss
Maintenance			
Special self-cleaning treatment		■	■
FIRE SAFETY			
Reaction to fire classification	EN 13501-1	A2-s1,d0	A2-s1,d0

□ MOQ applies. Please contact Rockpanel for further details.
■ Standard
O on request
- not available

Design facades				Premium
Rockpanel Colours	**Rockpanel Colours Protect Plus**	**Rockpanel Metals**	**Rockpanel Chameleon**	**Rockpanel Premium**
■	■	■	■	■
■	■	■	■	■
■	■	■	■	
■	■	■	■	■
–	–	–	–	–
■	□	■	■	■
■	□	□	□	□
□	□	□	□	□
□	□	□	–	□
8 & 9	8 & 9	8 & 9	8 & 9	11
–	–	–	–	–
–	–	–	–	–
RAL, NCS	RAL, NCS	Metallic & patina look	Chameleon effect	All Rockpanel Designs
–	○	–	–	■
○	○	○	○	□
3-4 or better	4 or better	4 or better	4 or better	4 or better
Semi-gloss Matt, High-gloss	Semi-gloss Matt, High-gloss	Matt, Semi-gloss (depends on design) Matt, Semi-gloss, High-gloss	High-gloss Matt, Semi-gloss	Depends on Design
Available with Protect Plus	■	■	■	■
A2-s1,d0	A2-s1,d0	A2-s1,d0	A2-s1,d0	A2-s1,d0



TECHNICAL **GUIDE.**





INDEX

1	The ventilated facade and its many advantages	92
1.1	Types of cladding installations	97
1.2	Specifications for sub-constructions	105
1.3	Joints and jointless applications	108
2	Working with Rockpanel	111
2.1	Sawing	112
2.2	Edge solutions and profiles	114
2.3	Fixing technology	116
2.3.1	Types of fixings	116
2.3.2	Drilling	118
2.3.3	Mechanical fixing on timber sub-constructions	119
2.3.4	Mechanical fixing on aluminium sub-constructions	120
2.3.5	Mechanical fixing on steel sub-constructions	121
2.4	Fixing guidelines	122
2.4.1	Tension free fixing	122
2.4.2	Guidelines and fixing distances	124
2.4.3	Determining the fixing distances	126
2.5	Bending	133
2.6	Handling of Rockpanel boards	134
3	Maintenance and Recycling	137
4	Planning details (CAD)	142
5	Further planning services	166

1 The ventilated facade and its many advantages

A ventilated facade is a facade construction with an air gap between the insulation and the facade cladding. This gap is open at the top and bottom and the cladding has small open joints. This creates a way for natural ventilation of the facade.

A ventilated facade can be viewed as a raincoat: it protects a building against the weather, while at the same time creating a healthy indoor climate. This is why the building technique of ventilated facades is often referred to as rainscreen cladding.




Protects the building against weather



The ventilation effect through behind and through the joint of the cladding

Natural ventilation

A ventilated facade protects the building against weather influences and has natural ventilation. Most of rain water will run down the outer surface of cladding boards. Small rain drops which enter the cavity or any condense water will drain off. With a well-designed and well-constructed ventilated facade, negative effects of condensation can be prevented, Vapour will escape quickly thanks to the ventilation flow within the cavity. Algae and moisture problems do not occur and mold cannot grow because of this ‘self-breathing’ effect of the facade.



A stone wool insulation effectively works against temperature and noise

Healthy indoor climate

Using a ventilated facade construction helps creating a healthy indoor climate. A ventilated facade reduces the direct solar impact on the building. Walls do not heat up as much during summer, thanks to the constant air flow in the cavity which is constantly cooling the construction.

Insulating effect and protection

Ventilated facades provide great insulation and contribute to energy efficiency and cutting down exterior noise. The Rockpanel façade cladding effectively protects the insulation against weather influences such as rain, snow and wind.



Rockpanel designs make buildings unique

Lower construction and maintenance costs

Compared to a brick cavity wall, a ventilated facade is lighter, which can lower the construction costs. Rockpanel facade claddings offer intended working life of 50 years. All Rockpanel products are characterised by outstanding colour stability. Rockpanel with ProtectPlus coating offers a self-cleaning effect in the rain and makes it easy to remove graffiti.

Easy access

With a ventilated facade, there is easy access to the facade and to the construction behind it. It is also possible to hide rain water drainage pipes and other elements behind cladding boards. This comes in handy when any maintenance or refurbishment is required.



Freedom of design


Architects are very flexible in their design choices, with a wide range of colours and designs available for exterior Rockpanel cladding. It's also easy to replace the cladding at any point, providing even more flexibility in aesthetics. Rockpanel facade boards are available in over 200 colours and designs – and customizations are possible as well.



Ventilated facade construction can be demounted individually, which enables reusing and/or recycling them

Easy disassembly and recycling

All parts of a ventilated facade construction can be demounted individually, which enables reusing and/or recycling them. As Rockpanel boards are endlessly recyclable. They are the best choice for exterior cladding in your ventilated facade when it comes to sustainability and circularity.



Safe construction with an effective fire barrier behind the cladding

Fire safety

Rockpanel exterior cladding also stands out because of its excellent fire resilient qualities. The core material basalt can withstand extremely high temperatures by nature. Rockpanel cladding is available in Euroclass A2-s1,d0 and can be perfectly combined with stone wool insulation from ROCKWOOL.



VENTILATED
FACADES.

1.1 Types of cladding installations

Ventilated facade construction

Rockpanel serves as the cladding material in a ventilated facade system. This type of facade, also referred to as a rainscreen, acts as a secondary defence system. It features a ventilation cavity behind the cladding, allowing airflow that aids in the evaporation of moisture from condensation and rainwater.

Ventilation openings are necessary at both the bottom and top of the facade to allow for free airflow, with a ventilation cavity depth of minimum 20 mm required. Whether the facade features open or closed joints, it must include adequate ventilation openings and cavity depth.

For effective ventilation, the cavity must have ventilation openings of at least 5000 mm^2 per meter of length. Rockpanel recommends openings between 5 and 10 mm in width.

Additionally, it is recommended to apply an anti-insect mesh to deter insects and rodents from entering the ventilation cavity. (Please check your local regulations for any specific requirements)

Non-ventilated constructions

It is also possible to apply Rockpanel to a non-ventilated facade. Please visit our website for more information and preconditions.

Ventilated facades with Rockpanel cladding help to:

- Counterbalance the effects of moisture
- Reduce energy consumption year-round
- Enhance quality of living with aesthetic designs
- Prolong the lifespan of the facade
- Provide excellent climate and fire resilient properties

There are two types of constructions with specific demands:

Open facade construction

Page 99-101

Closed facade construction


Page 102-103



Open facade construction

An open facade system is applied with open joints. Therefore, there is a possibility of some rainwater entering the cavity behind the panels. Any water that penetrates needs to be guided out of the facade and drain away. Furthermore, it's important to close off air cavities at the corners of the building using cavity closers, helping to prevent any increase in wind load.

Cavity closers need to be correctly applied (1) & (2).




1. Cavity closer correctly applied

Pressure Equalization

To calculate the correct fixing distances with pressure equalization, aimed at reducing wind load and achieving wider fixing distances, application must adhere to be the following preconditions:

- Horizontal open joints of 5-10mm
- Open joints represent ≥ 0.10 % of the total surface
- Cavity closers should be used to prevent accumulation of wind loads (see also drawing)
- The depth of the ventilation cavity should be at least 40 mm deep (maximum 100 mm)
- UV-resistant breathable membrane (in case of timber sub-construction).



2. Cavity closers missing will lead to wind load issues

Open facade construction - Horizontal joints


In an open facade, horizontal joints should have a minimum width of 5 mm.

Timber sub-construction (1)

For a timber sub-construction the maximum width can be 8 mm.

In a timber sub-construction with open joints, the structure behind the vertical batten should be protected with a breathable, water-repellent, and UV resistant membrane.

The cavity between the Rockpanel board and the breathable membrane should be minimum 25 mm or greater to accommodate the required thickness of the battens.




1. Timber sub-construction, open horizontal joint

Metal sub-construction (2)

For a metal sub-construction the maximum width of open horizontal joints can be 10 mm.

The minimum cavity depth is 20 mm, but Rockpanel recommends a cavity depth of 40 - 100 mm, to ensure adequate pressure equalisation and to prevent of excessive rainwater penetration.




2. Metal sub-construction, open horizontal joint.

Open facade construction - Vertical joints

Vertical joints in this type of construction are closed by the backing of the vertical sub-construction.

Timber sub-construction (3)

To ensure the durability of a timber sub-construction , the vertical battens require adequate protection against rainwater. This can be achieved by using a UV- and weather-resistant EPDM gasket that extends 15 mm wider on both sides than the framework.




Joint 5-8 mm

3. Timber sub-construction vertical joint with gasket

Metal sub-construction (4)

The vertical joints of a metal sub-construction are closed with an aluminium or galvanized steel profile, here is no EPDM gasket needed.




Joint 5-10 mm

4. Metal sub-construction, open vertical joint.


Closed facade construction

In a closed facade system, the supporting structure must be well ventilated. This entails maintaining a cavity of at least 20 mm behind the cladding, with minimum continuous opening of 5 (or equivalent slots) at top and bottom. For timber sub-construction, a cavity of 25 mm is necessary, considering the minimal thickness of the batten.

Timber subconstruction (1 & 2)



1. Timber sub construction with closed horizontal joint




2. Timber sub construction with semi-closed horizontal joint

Horizontal joints

In a closed facade the horizontal joints are closed with a profile, usually a chair shaped profile ((1/3) Rockpanel Profile A) or bird nose shaped ((2) Rockpanel Profile B) - semi-closed.

This ensures that rainwater is effectively drained away on the outer side of the cladding.

Metal subconstruction (3)



3. Metal sub-construction vertical joint


Closed facade construction - Vertical joints

In this construction type, vertical joints are sealed by the the vertical sub-construction.

For further technical support regarding these types of constructions or other alternative applications, please see our website or contact Rockpanel for advice.
info@rockpanel.com

Timber sub-construction (4)

To enhance the durability of a timber sub-construction , the vertical battens must be well protected against rainwater. This can be achieved using a UV- and weather-resistant EPDM gasket. In the case of a closed horizontal joint, the gasket does not need to protrude.




Joint 5-8 mm

4. Timber sub-construction, vertical joint solution with EPDM gasket.

Metal sub-construction (5)

The vertical joints of a metal sub-construction are closed with an aluminium or galvanized steel profile, here is no EPDM gasket needed.



Joint 5-10 mm


5. Metal sub-construction vertical joint solution


SUB-
CONSTRUCTIONS.


1.2 Specifications for sub-construction

Rockpanel can be applied to sub-constructions made of either timber, aluminium or steel. For detailed information about sub-construction materials, please consult the European Technical Assessment (ETA) of the relevant Rockpanel product and your sub-construction supplier.

Timber



Metal (Aluminium, steel)




Quality of sub-constructions


Timber sub-construction (1 & 2)

Timber stud walls and timber battens fixed to inner leaf walls should be constructed in accordance with EN 1995-1-1 for design of timber structures. It is important to use suitable preservative treatments in compliance with EN 335 and local buildings standards and local regulations. Studding and framing must be adequately reinforced by noggings to guarantee rigidity.


In instances where timber stud walls or battens are treated with cuprous preservatives, it is crucial to allow sufficient time for the preservative to adequately condition before fixing the cladding.



Timber sub-construction



1. Fixing on supporting batten (min. 45x25mm)



2. Fixing on board batten (min. 70x25mm) behind a joint

Aluminium sub-construction

When Rockpanel boards are applied to an aluminium sub-construction, the sub-construction needs to fulfil the following minimum requirements:

- The aluminium alloy is AW-6060 according to BS EN 755-2:
  - $R_m/R_{p0.2}$ value is ≥ 170/140 for profile T6
  - $R_m/R_{p0.2}$ value is ≥ 195/150 for profile T66

- The minimum thickness of the profile is 1.5 mm for rivets and 1.8 mm for screws.

Steel sub-construction


The minimum thickness of the vertical steel profiles is either:

- 1.0 mm (for steel quality minimal S280GD +Z EN 1.0346 number 1.0250, or equivalent for cold forming) or

- 1.5 mm (for steel quality EN 10025-2:2004 S235JR number 1.0038)

The minimum coating thickness (Z or ZA) is determined by the corrosion rate, which varies based on the corrosion loss in thickness per year, depending on the specific outdoor atmospheric environment. The International Zinc association can be consulted for more information.

The coating designation, which determines the coating mass, should be agreed upon between the contractor and the building owner. Alternatively, a hot-dip galvanized coating according to EN ISO 1461 can be used.



Metal sub-construction (aluminium, steel)

1.3 Joints and jointless applications

The purpose of joints in a ventilated facade construction

Dimensional stability, or resistance to changes in length and width, is determined by a material's tendency to expand as a result of temperature and/or moisture (moisture absorption). The unique composition of Rockpanel means that the boards are virtually immune to dimensional change caused by temperature or relative humidity.

Thanks to the source material basalt, Rockpanel is dimensionally stable. Extreme temperature or humidity fluctuations cause practically no change to the length or width of the panels. Since the coefficient of expansion is even lower than that of concrete, Rockpanel boards undergo hardly any dimensional change.


It is possible to work with narrow joints of 5-6 mm, and in some applications, joint-free assembly is even possible.

- Take into account that boards, installation and building tolerances play an important role in the detailing of joints.
- The joints should be equal to or bigger than 5 mm, to ensure proper drainage.
- In wooden sub-constructions apply weather- and UV-resistant EPDM gasket on the battens behind the joints to protect the sub-construction against weather influences.

Low expansion, thinner joints

Due to the low expansion abilities of Rockpanel thinner joints are possible compared to alternative materials.

This allows to realize facades with a more closed, harmonic appearance.
With Rockpanel the minimum joint width starts from 5mm, for other materials joints below 10mm are not applicable due to the risk of damages due to expansion.



1. Rockpanel: High dimensional stability allows narrow joints between boards.



2. HPL and fibre cement boards: Joints need to be at least 10 mm wide.

Jointless installations

Rockpanel retains its shape as it is able to withstand moisture and changes in temperature. This allows it to be used seamlessly under certain conditions:

- Only for the use around the roofline, such as to finish guttering, for fascias and barge boards.
- Up to a maximum length of 12 metres
- Only when a timber subframe is used with vertical battens to prevent the subframe from warping
- The timber subframe has to be protected by using EPDM foam gaskets for all joints on the subframe
- Expansion joints are used throughout the Rockpanel construction. If there are expansion joints in the structure, the façade panels must also have expansion joints
- Only applicable with light colours



For further technical support regarding these types of constructions or other alternative applications, please see our website or contact Rockpanel for advice.
info@rockpanel.com



2 Working with Rockpanel

Your building concept lays the foundation

Beyond just colour and material, the facade design defines your building's identity, impacts its surroundings and follows function. With Rockpanel, you are in control – enjoy maximum design freedom at a lower cost.

Rockpanel offers flexibility

Should a specific panel format suit your facade design, we make it – customised to your needs. Thanks to the innovative production process, Rockpanel is available in all lengths between 1700 and 3050 mm. You decide which lengths are best for your particular design.

The facade fits into your vision and budget

Rockpanel is quick and easy to install. Due to its unique format, it is virtually waste-free and highly cost-effective. You will always find the solution that is exactly right for your building. Because it simply fits – into your design, your schedule and your budget.

Easy does it

Ensuring safe, efficient and fast handling of building materials is paramount in facade cladding. Rockpanel offers the durability of stone and is as easy to work with as wood. They are lightweight and can be machined quickly and easily. This saves installation time and makes your building more economical, without compromising on design, and functionality.



Working with standard tools

Rockpanel offers the robustness of stone but can be handled effortlessly. With quick and easy cutting, finishing and detailing, our boards can be prepared on site, saving you time and money during installation. Conventional tools such as high-quality hand saws, circular saws or jigsaws are all suitable.

Non-directional

Most Rockpanel facade panels are nondirectional, ensuring a consistent appearance regardless of how they are installed. This guarantees more efficient and swifter installation since fitting is simplified and waste is reduced. Therefore during processing there is no marking of installation direction required. This applies to all Rockpanel Colours, as well as Rockpanel Metals Elemental Grey Aluminium and White Aluminium. All other Metals, Woods, Chameleon and Stones designs are considered to be directional. Colour deviations may become visible on the surface if panel directionality is not observed. To ensure proper orientation, observe the direction of the text on the protective film on the front side of the panels.

Shine with detailed solutions

Rockpanel boards enables swift and effortless implementation of any design and solution. They can be quickly and easily applied with screws, rivets, nails and concealed fixing. Simply cut the facade panels to size and secure them in place.

2.1 Sawing

Standard tools can be used for sawing Rockpanel or creating penetrations and cut-outs in the material. Generally, it is recommended to saw the boards with the decorative side facing upwards and with the protective film still in place. However when using a hand-held circular saw, it is advised to have the decorative side facing downwards. It is recommended to test different tooling to achieve the desired result. Experiment with machine settings and blades on a sample of Rockpanel before sawing larger amounts of boards. Different coatings will behave differently as to sawing with different tools. Additionally, sawing multiple layers at once might affect the quality of the cut.

Always ensure there is a clean workplace with a horizontal, flat and stable surface supporting the board.

Suitable equipment



- Hand saw, e.g. a hard point saw
- Fretsaw, e.g. a fine-toothed saw blade for metal or a saw blade with tungsten coating
- Circular saw, e.g. a fine-toothed Widia/Tungsten Carbide saw blade, for example a blade with 48 teeth and a diameter of 300 mm. Or a diamond blade for best results.
- CNC-machines
- Mitre saw for special edge solutions

Indoor sawing

Use dust-reducing sawing equipment in combination with an extraction hood in a well-ventilated room.

Outdoor sawing

Position the saw installation so that the wind blows away any dust from the sawing. Use dust-reducing sawing equipment if possible. Always immediately clean the dust after sawing and drilling.

Safety guidelines

- Use a dust mask (type FFP1)
- Use standard safety spectacles to protect the eyes from dust
- Wear gloves during sawing
- Always check special safety guidelines related to the tools you are using as well as the environment of your construction site

Rockpanel safe use instruction sheet can be provided on request

We like to support your design. In case you need an optimized cutting plan for your project, please contact Rockpanel for an advice. info@rockpanel.com



2.2 Edge solutions and profiles

Corners and edges as design elements

Joints and corners give the facade design a definite emphasis and are a clear, formal statement – for a special material. With Rockpanel, there is no necessity to treat the edges to protect them from moisture. Consider corner solutions for a more aesthetic appeal, adding depth and unique flair to your design. Maintain creative freedom in your facade design – right down to the smallest details. Enhance the edges with profiles in the panel colour or finish the edges with matching colour paint, further enhancing the overall look.

Untreated edge (1)

With Rockpanel, there is no need to protect edges from moisture. Left unfinished, the edges will naturally age within several weeks to a natural dark brown hue due to outdoor exposure.

Chamfering them is simple; you can use fine-grade sandpaper or the reverse (non-decorative) side of a leftover Rockpanel strip to lightly sand the edge.

Painted edge (2)

If required for aesthetic reasons edges can be painted in the corresponding RAL/NCS colour with Rockpanel edge paint. Please refer to the instructions delivered with the edge paint or on our website.


Mitre joint (3)

For the highly skilled installer, a mitre joint can be achieved with Rockpanel, thereby creating a precise and uniform finish. Important: the minimum panel thickness for this solution is 8 mm.

Aesthetical profile (4)


Trims and profiles made of high-quality aluminium are available in nearly all RAL/NCS colours to suit your design. Depending on the product and fixing method, you can choose joint, corner and connecting profiles.

Profiles available from Rockpanel see page 83.





1. Untreated edge



2. Painted edge



3. Mitre edge



4. Aesthetical profiles


2.3 Fixing technology

2.3.1 Types of fixings


Rockpanel can be mounted in various ways including, screws, nails, rivets and invisible fixing. You are free to choose. These can be matched to help blend with the facade colour or deliberately contrast it. For a subtler approach, nails can also be used which are barely visible. Invisible fixing is also an option: with our adhesive system as specified in our certification. Lastly, our concealed fixing system enables you to easily create a flawless facade with invisible mechanical fixing.

Always ensure with the fixings supplier the suitability of their fixings to meet the technical requirements of Rockpanel as documented in the Declaration of Performance (DoP). Please check that fixings are suitable for the design and its associated performance requirements. It is further recommended to use only coloured fixings with a durable finish. Working with fixings from other manufacturers should be carried out according to their recommendations and supervision.


Screw fixed to timber




Nail fixed to timber



Adhesive system on timber



PlankClip on timber (with insulation)



Rockpanel nail
– nearly invisible


Rockpanel screw
– small head




Standard screw head used with other cladding materials




Screw fixed to metal




Rivet fixed to metal




Concealed fixing



Adhesive system on Aluminium



PlankClip on aluminium





Nails with matching colour



Screws with matching colour



Concealed fixing - not visible from the outside



Rivets in matching colour

2.3.2 Drilling

Pre-drilling of Rockpanel (when applied on timber sub-construction) is recommended by ETA. Holes for screws and nails should be pre-drilled with an HSS-steel drill. Diameter of the holes for fixed points, moving points and slotted holes needs to be according ETA.

Pre-drilling of Rockpanel (when applied on metal sub-construction) is always required. With rivets, fixed anchorages are advised to be drilled at Ø 5.2 mm and a moving point with Ø 8 mm. Predrilling can be done with a HSS-steel drill.

Mechanical fasteners, gaskets, adhesives with primers, strips for bonding, and sub-construction profiles are specified by the ETA-holder. For more information please refer to the Product Data Sheet or consult the appropriate ETA, available on our website www.rockpanel.com

Rockpanel screws, nails and rivets are available perfectly fitting to the board designs




Drill hole diameter (mm) according to ETA						
Type of fastener	**Rockpanel A2 8 mm**					**Rockpanel A2 11 mm**
Fastener	Rivet	Screws for aluminium (a)	Screws for steel	High performance Nail	Screws for timber	Rivet
Fixed point	5.1	5.8	4.3	2.5	3.2	5.1
Moving point	8.0	10.0 (b)	8.0	3.8	6.0	8.0
Slotted hole	5.1 x 8.0	-	4.3 x 8.0	2.8 x 4.0	3.4 x 6.0	5.1 x 8.0

(a) : The self-drilling screw for aluminium should always be fastened with 2 fixed points on the same horizontal level, max width 600 mm.
(b) : With the use of a centering sleeve.

2.3.3 Fixing on timber sub-constructions

Mechanical fixing to timber can be carried out with nails or screws. For a perfect match to the board material, the nail and screw heads can be provided with matching colours.



Screws for timber sub-construction

Rockpanel Torx screws - 4.5 x 35 mm.
stainless steel material number 1.4401 or 1.4578.
Screw Ø 9.6 mm (head diameter)




Adhesive fixing for timber sub-construction

Rockpanel is suitable for bonded application. There is over 25 years good experience with the bonding of Rockpanel. With Rockpanel A2 8 mm we offer a fire safe solution, with a reaction to fire classification of A2-s1,d0 onto timber sub-constructions (with intermediate Rockpanel strip).

For the latest information and guidelines of this application, in accordance with the applicable European Assessment Document, please visit the Rockpanel website and check the ETA-24/0910 for the certified bonding system.


If you wish to use an alternative bonding system not mentioned in this ETA, always verify with the system supplier whether this is technically approved and guaranteed for bonding Rockpanel boards. The bonding supplier is responsible for certification and guarantee. The quality of the bonded installation is partly determined by the weather conditions during application. For more information, refer to the bonding supplier.



PlankClip on timber sub-construction

The concealed, mechanical fixing system for horizontal or vertical planks / lamellas offers you exceptional design freedom thanks to a wide range of offset options on the façade. With narrow joints of 6 mm, you can create a modern appearance that meets the highest aesthetic demands. The system allows the installation of 9 mm thick panels in heights from 100 mm to 300 mm, whereby different panel-lengths can be combined to create a visually appealing laying pattern. The PlankClip is suitable for both timber and aluminium subconstructions, resulting in an A2-s1,d0 end-use fire class rating.


The fixing system is available as a kit, consisting of RCLIP (h 100 mm x d 40 mm x w 36 mm), RCLIP-SHORT (h 60 mm x d 42 mm x w 36 mm), TU-S anchor (6x9 mm) and SDAW fastener (4.5 x 34 mm).



Nails for timber sub-construction

Rockpanel nails can be attached with either a nylon hammer or nail gun. Rockpanel High Performance nails - 2.7/3.1 x 35 mm (flat top) stainless steel material number 1.4401 or 1.4578. Nail Ø 6.0 mm (head diameter)

2.3.4 Fixing on aluminium sub-constructions




Rivets for aluminium sub-construction

For mounting on an aluminium load-bearing sections the following aluminium rivets should be used: For Rockpanel A2 8 mm, please use SFS AP14-50180-S or MBE FN-AL5-5x18 K14. For Rockpanel Premium A2 11 mm, please use SFS AP14-50210-S or MBE FN-AL5-5x21 K14 Aluminium rivets, according to ETA.

With the following specifications:


- Head of the rivet: Ø 14 mm flat-topped
- Body of the rivet aluminium EN AW-5019 (AlMg5) in accordance with EN 755-2
- Mandrel stainless steel material number 1.4541 in accordance with EN 3506-1

For correct fixing, a riveting tool with rivet spacer and centre tool must be used. When installing Rockpanel boards on aluminium load-bearing sections, fixed points, slotted holes and moving points should be applied.



Screws for aluminium sub-construction


For the installation of Rockpanel A2 8 mm on aluminium load-bearing sections, aluminium self-drilling centre screws must be used: SFS screw code: SDA4-D15-CS10/8-5.8x29-A4. Center screw with centering sleeve. Screw head: 15 mm flat-topped. Body of screw: Stainless steel A4 in accordance with EN ISO 3506



Concealed fixing on aluminium sub-construction

For mounting of Rockpanel Premium with invisible concealed fixing on aluminium load-bearing sections TU-S 6x13 blind fastener is used for the secret fixing clip in thickness of 5 mm or TU-S-6x11 blind fastener for fixing clip in thickness of 3 mm. The Body of the blind fastener is made of stainless steel material number 1.4401 in accordance with EN 10088, with electro-galvanised carbon steel mandrel.

See ETA or contact us for more information.




Adhesive fixing on aluminium sub-construction

Rockpanel is suitable for bonded application. There is over 25 years good experience with the bonding of Rockpanel. With Rockpanel A2 8 mm we offer a fire safe solution, with a reaction to fire classification of A2-s1,d0 onto aluminium.

For the latest information and guidelines of this application, in accordance with the applicable European Assessment Document, please visit the Rockpanel website and check the ETA-24/0910 for the certified bonding system.

If you wish to use an alternative bonding system not mentioned in this ETA, always verify with the system supplier whether this is technically approved and guaranteed for bonding Rockpanel boards. The bonding supplier is responsible for certification and guarantee. The quality of the bonded installation is partly determined by the weather conditions during application. For more information, refer to the bonding supplier.




PlankClip for aluminium sub-construction

The concealed, mechanical fixing system for horizontal or vertical planks / lamellas offers you exceptional design freedom thanks to a wide range of offset options on the façade. With narrow joints of 6 mm, you can create a modern appearance that meets the highest aesthetic demands. The system allows the installation of 9 mm thick panels in heights from 100 mm to 300 mm, whereby different panel-lengths can be combined to create a visually appealing laying pattern. The PlankClip is suitable for both timber and aluminium subconstructions, resulting in an A2-s1,d0 end-use fire class rating.

The fixing system is available as a kit, consisting of RCLIP (h 100 mm x d 40 mm x w 36 mm), RCLIP-SHORT (h 60 mm x d 42 mm x w 36 mm), TU-S anchor (6x9 mm) and SDAW fastener (4.5 x 34 mm).

2.3.5 Mechanical fixing on steel sub-constructions




Rivets for steel sub-construction

For mounting Rockpanel on steel load-bearing sections the following stainless steel rivets should be used; Rockpanel A2 8 mm boards, SSO-D15 50180 or MBE FN-A4-5x18 K15. For Rockpanel Premium A2 11 mm, please use SSO-D15 50210 or MBE FN-A4-5x21K15. Stainless steel rivets should be used according to ETA.

With the following specifications:


- Head of the rivet: Ø 15 mm flat-topped
- Body of the rivet stainless steel material number 1.4578 in accordance with EN 10088
- Mandrel stainless steel material number 1.4541 in accordance with EN 3506-1

For correct fixing, a riveting tool with rivet spacer and centre tool must be used. When installing Rockpanel boards on steel loadbearing sections, fixed points, slotted holes and moving points should be applied.



Screws for steel sub-construction

For the mounting of Rockpanel A2 8 mm on steel load-bearing sections, steel EJOT screws JT6-FR-3-5.5x35 and JT6-FR-3-5.5x25 can be used.





2.4 Fixing guidelines

2.4.1 Tension free fixing

Cladding boards must be mounted without tension. Regardless of the type of the sub-construction, fixings should be applied according to good building practices, avoiding overtightening. If tension occurs for instance due to differences in elongation between a sub-construction and the cladding boards, fixed points, slotted holes, and moving points must be applied. Fixed point, slotted hole and moving points can be applied in several ways.

Principle

Each panel, regardless of size, will have either two fixed points or one fixed point combined with one or two slotted points. These fixed points and slotted points support the weight of the panel and ensure it remains securely in position. All others will be moving points.

Key fixing possibilities:
MP = Moving point, Ø according to ETA
FP = Fixed point or fixed point created by sleeve, Ø according to ETA,
SP = Slotted point or slotted point created by sleeve, dimensions according to ETA.

Correct application of the slotted point and moving point:

- Preventing clamping of the fastener: To avoid clamping of the fastener caused by over-tight rivets, it is needed to use a rivet spacer. The rivet spacer ensures a 0.3 mm distance between the head of the rivet and the surface of the Rockpanel board, allowing the rivet to move freely in the moving points.
- Ensuring fastener movement: Fasteners located in slotted holes or moving points must be able to move. Position the fastener exactly in the middle of the slotted hole or moving point. To ensure the fastener is exactly in the middle, a centre tool or centre drill should be used.
- Arranging fixed points: Whenever possible, fixed points should be placed in the centre of the facade panel, ideally symmetrically and always close to a horizontal centre line of the board.


Helpful tips for a simple and speedy installation

You can drill holes directly into the board for fixed points, moving points, and slotted points. For slotted holes, you can create them using a router. Alternatively, you can drill all the holes as moving points, after which a sleeve can be used to narrow the hole to create the fixed points or slotted points. Different sleeves are available for fixed points and slotted points. In the event of using sleeves it should be considered that the maximum distance between a fixed point and a side sleeve (sleeve used in the slotted point) is limited to 600 mm. For correct application of the sleeves a proper positioning tool should be used


Examples for a correct vertical or horizontal orientated application.

Examples for vertically orientated boards ≥ 8 mm:

1. Combination fixed point and slotted points




2. Combination of 2 fixed points




Examples for horizontally orientated boards ≥ 8 mm:


3. Combination fixed point and slotted points in a symmetric way



4. Combination fixed points and slotted point in a symmetric way



5. Combination of fixed and slotted point in an asymmetric way



MP = Moving point, Ø according ETA

FP = Fixed point or fixed point created by sleeve, Ø according ETA

SP = Slotted point or slotted point created by sleeve, Ø according ETA


2.4.2 Guidelines and fixing distances

In this section the mounting guidelines and maximum fixing distances are indicated for facade panels A2 8 mm on timber support structures and for facade elements on aluminium support structures on the basis of boundary conditions, data and material properties.

Maximum fixing distances between fastening points according to ETA: The table below shows the maximum fixing distances at a vertical timber sub-construction or aluminium sub-construction in accordance with

- ETA-24/0910: Rockpanel Colours, Chameleon, Metals, Stones and Woods A2 8 mm
- ETA-18/0883: Rockpanel Premium A2 11 mm with visible fixing
- ETA-25/1032: Rockpanel Premium A2 11 mm with concealed fixing

For all medium and high rise buildings, we recommend the use of our A2 grade boards (A2-s1,d0). Project specific calculations are available on request.



Edge distance a_{R1}	For A2 8 mm Timber: ≥15 mm Metal: ≥20 mm
Edge distances a_{R2}	≥50 mm

Maximum fixing distances according to ETA

Rockpanel board	Sub-construction	Fastener	Maximum span (b)	Maximum vertical distance between fasteners (a)
Premium A2 11 mm	Aluminium/Steel	Rivets	750 mm	750 mm
	Aluminium	Blind fastener	750 mm	600 mm
Rockpanel A2 8 mm	Timber	High performance nail	600 mm	400 mm
	Timber/Aluminium/Steel	Screw	600 mm	600 mm
	Aluminium/ Steel	Rivet	600 mm	600 mm
	Timber/Aluminium	Adhesive system	600 mm	Continuous application of adhesive

Ceiling applications

If applying Rockpanel for a ceiling application, the specific weight of the board must be taken into account in the calculation of the fixing distances.
As a general guideline, you can multiply the fixing distances by 0.75.



2.4.3 Determining the fixing distances

The following steps should be followed to determine the fixing distances:

Determine the design wind load

1. **Define wind zone (Step 1)**
   Find the place where the project is located on the country map and note the relevant wind speed zone

2. **Define terrain category (Step 2)**
   Find the relevant terrain type in the overview of various terrain categories

3. **Define area on the façade: (Step 3)**
   Define the area on the facade, Zone A or B. Zone A is decisive for keeping the fixing distances the same over the entire facade.


- Zone A for corner area
- Zone B for middle area

Consider the rules in standard EN 1991-1-4). If unknown or facades are very small use zone A as normative value.

4. **Look up the design wind load in kN/m² in the table (Step 4)**

For further technical support regarding calculations, please contact Rockpanel for advice
info@rockpanel.com

Step 1. Wind zones and basic wind velocities :




This map is an indication of the fundamental basic wind velocity according to BS-EN 1991-1-4. If you are unsure which zone the building is located please contact Rockpanel.

Step 2. Define terrain category

Terrain category (countryside)
Specified by the distance upwind to shoreline (km).

Terrain category (town)
Town located 10-100 km upwind to shoreline. Specified by the distance of the building into town (km).

Step 3. Define area on the facade



Step 4. Look-up the wind load

Value of fundamental basic wind velocity $v_{b,map}$(m/s)

United Kingdom		1) Wind Zone	28		26		25		23		22	
		3) Facade area	A	B	A	B	A	B	A	B	A	B
2) Terrain category												
Terrain Category - Countryside	Distance upwind to shoreline	≤0.1 to 1 km	-2.64	-1.76	-2.28	-1.52	-2.11	-1.41	-1.78	-1.19	-1.63	-1.09
		1 to 10 km	-2.57	-1.71	-2.22	-1.48	-2.05	-1.37	-1.73	-1.16	-1.59	-1.06
		10 to 100 km	-2.33	-1.55	-2.01	-1.34	-1.85	-1.24	-1.57	-1.05	-1.44	-0.96
		≥100 km	-2.18	-1.46	-1.88	-1.26	-1.74	-1.16	-1.47	-0.98	-1.35	-0.90
Terrain Category - Town located 10-100 km upwind to shoreline	Distance into town (km)	≤0.4 km	-2.33	-1.55	-2.01	-1.34	-1.85	-1.24	-1.57	-1.05	-1.44	-0.96
		0.4 to 1 km	-2.31	-1.54	-1.99	-1.33	-1.84	-1.23	-1.56	-1.04	-1.43	-0.95
		1 to 5 km	-2.14	-1.43	-1.84	-1.23	-1.71	-1.14	-1.44	-0.96	-1.32	-0.88
		≥5 km	-1.92	-1.28	-1.66	-1.11	-1.53	-1.02	-1.30	-0.87	-1.19	-0.79

Note: Building height ≤ 10 m / Site altitude ≤ 50 m

All information in this calculation is protected by copyright. This calculation does not constitute a static verification and is purely intended as orientation. The greatest possible care has been taken in determining the calculation method and the calculation. However, ROCKWOOL B.V / Rockpanel cannot warrant the completeness and accuracy of the information stated, the performance of its products, the calculation and/or any advice based on this. All calculations and statements relating to performance are approximations and will not bind ROCKWOOL B.V / Rockpanel. Customers are recommended to have our calculation and/or technical advice on their specific projects confirmed by the involved architects, specialist engineers, designers and/or contractors. For high-rise buildings and high-risk buildings Rockpanel recommends the application of non-combustible (Euroclass A1-A2-s1, d0) cladding and insulation.


Step 5. Choose the correct table by:


- Type of board and thickness e.g., Rockpanel A2 8 mm
- Load absorption due to static scheme with 1 or 2- or more field span (5)
- Type of fastening system (e.g.)
- Timber with screws
- Aluminium with rivets

Step 6. Look up the max vertical distance possible and preferred span


- Use the wind load calculated in step 4
- Look up the centre-to-centre distance between the vertical sub construction (timber battens or metal profiles)
- Define the maximum fixing distance between the fasteners within the table


1-field-span





2- or more field-span






Step 5. Static schemes

Example 1

Calculation of fixing distances

Coated Rockpanel A2 boards, 8 mm thickness

1-field span



- ETA-24/0910
- Cavity closers (on the corners of the building) applied
- Maximum deflection of the panels 0.75 %
- Thickness gasket max. 0.5 mm
- Sub-construction: see table
- If the table shows no fixing distance (-) or building height > 10 m, please contact Rockpanel for the possibilities and specific advice.

Fasteners: Screws on timber

Maximum fixing distance a of screws (mm) for different centre-to-centre distances (b) of the vertical substructure (k_{mod} : 1.00)

Timber quality: ≥ C18, utilisation class 2 according to EN 1995-1-1

b (mm)	Design wind load on Rockpanel board ($F_d = F_{rep} * \mu_F$) in kN/m²												A2 8 mm			
	-0.80	-0.90	-1.00	-1.10	-1.20	-1.30	-1.40	-1.50	-1.60	-1.70	-1.80	-1.90	2.00	-2.10	2.20	-2.30
600	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–
500	600	600	600	600	–	–	–	–	–	–	–	–	–	–	–	–
400	600	600	600	600	600	600	600	600	600	600	565	540	515	490	465	445
300	600	600	600	600	600	600	600	600	600	600	600	600	600	600	600	575

Fasteners: Rivets on aluminium

Maximum fixing distance a of rivets (mm) for different centre-to-centre distances (b) of the vertical substructure

Aluminium sub-construction according to ETA

b (mm)	Design wind load on Rockpanel board ($F_d = F_{rep} * \mu_F$) in kN/m²												A2 8 mm			
	-0.80	-0.90	-1.00	-1.10	-1.20	-1.30	-1.40	-1.50	-1.60	-1.70	-1.80	-1.90	2.00	-2.10	2.20	-2.30
600	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–	–
500	600	600	600	600	–	–	–	–	–	–	–	–	–	–	–	–
400	600	600	600	600	600	600	600	600	600	600	600	600	590	565	540	515
300	600	600	600	600	600	600	600	600	600	600	600	600	600	600	600	600

Legend:

a Vertical distance between fasteners

b Distance of the vertical sub construction carriers

a_{R1} - Timber ≥ 15mm
- Metal ≥ 20mm

a_{R2} Edge distance top/ bottom ≥ 50 mm

k_{mod} Modification coefficient for load duration and moisture content


Example 2

Calculation of fixing distances

Coated Rockpanel A2 boards, 8 mm thickness

2-field span

- ETA-24/0910
- Cavity closers (on the corners of the building) applied
- Maximum deflection of the panels 0.75 %
- Thickness gasket max. 0.5 mm
- Sub-construction: see table



Fasteners: screws on timber

Maximum fixing distance a of screws (mm) for different centre-to-centre distances (b) of the vertical sub-construction

Timber quality: ≥ C18, utilisation class 2 according to EN 1995-1-1

b (mm)	Design wind load on Rockpanel board ($F_d = F_{rep} * \mu_F$) in kN/m²												A2 8 mm			
	-0.80	-0.90	-1.00	-1.10	-1.20	-1.30	-1.40	-1.50	-1.60	-1.70	-1.80	-1.90	2.00	-2.10	2.20	-2.30
600	585	515	465	425	390	360	340	315	295	–	–	–	–	–	–	–
500	600	600	560	510	465	430	405	375	355	335	315	300	285	275	260	250
400	600	600	600	600	580	540	500	465	440	415	390	370	355	335	325	310
300	600	600	600	600	600	600	600	600	585	550	520	495	470	445	425	410

Fasteners: rivets on aluminium

Maximum fixing distance a of rivets (mm) for different centre-to-centre distances (b) of the vertical substructure

Aluminium sub-construction according to ETA

b (mm)	Velocity pressure on Rockpanel A2 8 mm ($F_d = F_{rep} * \mu_F$) in kN/m²												A2 8 mm			
	-0.80	-0.90	-1.00	-1.10	-1.20	-1.30	-1.40	-1.50	-1.60	-1.70	-1.80	-1.90	2.00	-2.10	2.20	-2.30
600	600	575	520	475	435	400	375	350	330	–	–	–	–	–	–	–
500	600	600	600	565	510	480	445	415	390	370	350	330	315	300	290	275
400	600	600	600	600	600	595	555	520	485	460	435	410	390	375	355	345
300	600	600	600	600	600	600	600	600	600	600	575	545	520	495	475	450

Legend:

a Vertical distance between fasteners

b Distance of the vertical sub construction carriers

a_{R1} - Timber ≥ 15mm
- Metal ≥ 20mm

a_{R2} Edge distance top/ bottom ≥ 50 mm

k_{mod} Modification coefficient for load duration and moisture content



ROCKWOOL Nordics, Hedehusene, Denmark


See Rockpanel website for additional fixing distances for other

- Board types
- Static schemes
- Fastening systems









2.5 Bending

Naturally bend, shape and curve

If you feel that nature is the greatest architect, then choosing Rockpanel follows perfectly with this belief. With Rockpanel facade panels, you can bring any vision you have for your building to life.

Share the narrative of your architecture directly on its surface, creating captivating features with fluid, organic forms. Sculpt Rockpanel facade panels into any configuration you desire, whether it's a graceful curve or even a perfect circle.


Technical requirements

- When using Rockpanel A2 8 mm, it is possible to create designs with a radius exceeding 2500 mm. Our facade panels can be easily bent and curved without any additional treatment. The recommended minimum bending radius is determined by the bending strength of Rockpanel boards and must be bent lengthwise.
- Note: Rockpanel does not recommend bending boards on an aluminium sub-construction. It is the responsibility of the engineer to decide whether it can be done tension-free with a steel sub-construction.

Rockpanel Colours, Chameleon, Metals, Stones & Woods	
Panel thickness (mm)	8
Panel length (curve, mm)	3050
Radius R minimal (mm)	2500
Corner α	69.9°
Chord (mm)	2864
Level (mm)	451
Battens c.t.c. (mm)	400
Fixings c.t.c. (mm)*	300

* Indication for the fixing distances in urban and rural environments with building heights ≤ 10 m. When Rockpanel is applied in bent or curved conditions on higher buildings or in environments with a higher wind load, please contact Rockpanel.

For further technical support regarding these types of constructions or other alternative applications, please see our website or contact Rockpanel for advice. Info@rockpanel.com



2.6 Handling of Rockpanel boards

Packaging and storage

Rockpanel is a light-weight, decorative external cladding product which weighs less than many other board materials. The products should always be handled with care by taking the following guidelines into account:

- Storage in warehouse and building site (1 - 4)
- On site handling (5 & 6)


Handling of the protective film

- Most Rockpanel boards are covered by a film to protect the decorative finish. Site measurements can also be marked on this film to aid the installation process. If you're marking anything on protective film, it's advisable to test the pen on a sample board first. This step ensures compatibility and helps prevent potential bleeding through. Some permanent markers may bleed through the film, so a preliminary test can save you from any unwanted surprises.
- Remove the protective film:
  - directly after mounting, if attaching mechanically with screws or manual nailing;
  - before priming the board for adhesive bonding, not required but recommended;
  - before installing when using a pneumatic hammer.
- The protective film can be recycled.
- Rockpanel Metals (White Aluminium and Grey Aluminium) are delivered without protective film. Handling of these boards needs extra care.




1.

Store the board material in dry, flat, frost-proof and protected from the weather. Do not wrap the boards, but cover them in a way that allows air circulation, aiding evaporation of humidity.




4.

Do not stack more than three pallets high. During storage, the board material can be more affected by moisture and night-time cooling than when installed. Before installing, the boards will need some time to allow any moisture and condensation to evaporate.




2.

Store on flat pallets and place the pallets on a level foundation. Preferably with PE-foil as an underlay.




3.

Make sure that the board material does not have direct contact with the floor.




5.

Individual panels must be lifted off the pallet by two people and carried upright. Do not pull or push the boards.



6.

Protective foam membranes should be placed between the sheets again to protect the surface layer. For example, when the panels are stacked after having been sawn.


MAINTENANCE.
CLEANING.
DISMANTLING

3 Maintenance and Recycling

Brave the elements - in the most beautiful way.

With a ventilated facade, you can protect the exterior insulation and the inside of your building from sun, rain and moisture. Rockpanel is – like all ROCKWOOL products – produced from the natural raw material basalt. This is the volcanic rock from which Rockpanel products derive their unique properties. The Rockpanel boards themselves are also equipped for all weather conditions.

- The surface permanently resists sun, wind and rain.
- This keeps the facade beautiful for the years to come.
- And in addition, Rockpanel boards are low-maintenance.

Colour stability

Rockpanel boards are treated with a water-based coating that maintains their appearance, colour and finish for years to come. The table below shows the performance of the Rockpanel boards after a weathering test of 3000 and 5000 hours. This represents the weathering on a vertical south-facing facade. The ProtectPlus coating is applied as standard on Rockpanel Premium, Woods, Stones, Metals and Chameleon.

Colour stability	**Unit: Greyscale**	
Rockpanel design:	**Value 3000 hours**	**Value 5000 hours**
Premium	4-5	4 or better
Colours	4	3-4 or better
Colours with ProtectPlus	4-5	4 or better
Woods	4-5	4 or better
Stones	4-5	4 or better
Metals	4-5	4 or better
Chameleon	4-5	4 or better



3.1 Cleaning

Rockpanel products generally require low maintenance, primarily needing only rain for cleaning. However, in cases where additional cleaning is necessary, such as from bird droppings or tree residue, annual inspections and occasional cleaning with mild, non-solvent based products are recommended.

Specific cleaning instructions vary by product type:

- Rockpanel Colours can be cleaned with lukewarm water and mild cleaning agents
- Rockpanel with ProtectPlus can handle anti-graffiti cleaners if needed
- Rockpanel Natural should be cleaned gently with a wire brush.


It is crucial to follow cleaning agent manufacturer instructions, conduct suitability tests on inconspicuous areas and avoid abrasive or high-pH cleaning agents. Always clean from top to bottom and avoid cleaning in extreme temperatures or direct sunlight. For more detailed cleaning and maintenance instructions visit our download section at https://www.rockpanel.com/support/resources/

ProtectPlus and graffiti removal

Even more protection: Rockpanel with Protect Plus finish

Rockpanel has products in the assortment that come as standard with a protective coating layer called ProtectPlus. This provides extra protection against things like UV light and graffiti. Did graffiti end up on Rockpanel products? You can use our anti-graffiti cleaner if needed (the cleaner leaves no traces or marks). Rockpanel Premium, Woods, Stones, Chameleon and Metals (except White Aluminium and Grey Aluminium) are coated with ProtectPlus as standard for anti-graffiti-purposes.

Rockpanel Colours can be optionally finished with a ProtectPlus layer.



Graffiti can be removed from Rockpanel boards coated with ProtectPlus.



3.2 Dismantling


Designed for disassembly.

Recycling is possible when building materials are designed for disassembly, making it easy to recycle them, rather than having to throw them away. For example, a ventilated facade with Rockpanel exterior cladding, an aluminum sub-construction, and ROCKWOOL insulation can be easily deconstructed and completely split into three clean and fully recyclable parts at the end of life of a building or in case a facade needs to be refurbished.


For each element of a ventilated façade system (decorative cladding, metal or timber sub-construction and insulation such as ROCWOOL) suitable ways to recycle are available. For Rockpanel and ROCKWOOL products we offer the Rockcycle system. For more details on how to dismantle Rockpanel, see our advice in the download section at https://www.rockpanel.com/support/resources/



Easy dismantling of Rockpanel boards





Rockpanel offers recycling abilities




4. CAD
DRAWINGS.

Rockpanel A2 8 mm
Timber subconstruction, mechanically fixed





A-A




B-B


Details:

H.01	Junction vertical joint
H.02	Window junction
H.03	External corner
H.04	Internal corner
V.01	Roof trim -parapet
V.02	Abutting pavement
V.03	Window header
V.04	Window-sill connection


Rockpanel A2 8 mm
Timber subconstruction, mechanically fixed, Section A-A




H.01 Junction vertical joint



H.02 Window junction




H.03 External corner




H.04 Internal corner


Rockpanel A2 8 mm
Timber subconstruction, mechanically fixed. Section B-B.




V.01 Roof trim -parapet



V.03 Window header




V.02 Abutting pavement




V.04 Window-sill connection


Descriptions

1	Rockpanel A2 8 mm
2	EPDM foam gasket
3	Air cavity
4	Breathable membrane
5	Insulation (ROCKWOOL)
6	Timber construction
7	Inner wall
8	Timber battens ≥ 25 x 45mm
9	Timber battens ≥ 25 x 70mm
10	Rockpanel fixing
11	Ventilation opening
12	Joint from 5 to 8 mm
aR1	≥ 15 mm
aR2	≥ 50 mm




Rockpanel A2 8 mm
Metal subconstruction, mechanically fixed.





A-A




B-B


Details:

H.01	Junction vertical joint
H.02	Window junction
H.03	External corner
H.04	Internal corner
V.01	Roof trim -parapet
V.02	Abutting pavement
V.03	Window header
V.04	Window-sill connection


Rockpanel A2 8 mm
Metal subconstruction, mechanically fixed, Section A-A




H.01 Junction vertical joint



H.02 Window junction




H.03 External corner




H.04 Internal corner


Rockpanel A2 8 mm
Metal sub construction, mechanically fixed. Section B-B




V.01 Roof trim -parapet



V.03 Window header




V.02 Abutting pavement




V.04 Window-sill connection

Descriptions


1	Rockpanel A2 8 mm
2	Air cavity
3	Insulation (ROCKWOOL)
4	Aluminium rail
5	Fixing (rivet/screw)
6	Joint from 5 to 10 mm
7	Ventilation opening
8	Ventilation profile/Anti-insect mesh
9	Windowsill with end dam
aR1	≥ 20 mm
aR2	≥ 50 mm



Rockpanel A2 8 mm
Timber subconstruction, adhesive system.



A-A



B-B

Details:

H.01 Junction vertical joint

H.02 Window junction

H.03 External corner

H.04 Internal corner


V.01 Roof trim -parapet

V.02 Abutting pavement


V.03 Window header

V.04 Window-sill connection


Rockpanel A2 8 mm
Timber sub construction, adhesive system. Section A-A




H.01 Junction vertical joint



H.02 Window junction




H.03 External corner




H.04 Internal corner


Rockpanel A2 8 mm
Timber subconstruction, adhesive system. Section B-B




V.01 Roof trim -parapet



V.03 Window header



V.02 Abutting pavement




V.04 Window-sill connection


Descriptions

1	Rockpanel A2 8 mm
2	Rockpanel strips
3	Air cavity
4	Breathable membrane
5	Insulation (ROCKWOOL)
6	Timber construction
7	Inner wall
8	Timber battens ≥ 25 x 45mm
9	Timber battens ≥ 25 x 70mm
10	Bondingsystem according supplier
11	Ventilation opening
12	Joint from 5 to 8 mm



Rockpanel A2 11 mm
Metal subconstruction, concealed fixing.





A-A




B-B


Details:

H.01	Junction vertical joint
H.02	Window junction
H.03	External corner
H.04	Internal corner
V.01	Roof trim -parapet
V.02	Abutting pavement
V.03	Window header
V.04	Window-sill connection


Rockpanel A2 11 mm
Metal sub construction, concealed fixing. Section A-A




H.01 Junction vertical joint



H.02 Window junction




H.03 External corner




H.04 Internal corner


Rockpanel A2 11 mm
Metal sub construction, concealed fixing. Section B-B




V.01 Roof trim -parapet



V.03 Window header



V.02 Abutting pavement




V.04 Window-sill connection


Descriptions

1	Rockpanel Premium A2
2	Air cavity
3	Insulation (ROCKWOOL)
4	Concealed fixing clip
5	Horizontal profile / rail
6	Vertical profile / rail
7	TU-S Blind fastener (undercut anchor)
8	Ventilation
9	Anti-Insect mesh
10	Cavity closure




Rockpanel A2 9 mm
PlankClip on timber.





A-A




B-B


Details:

H.01	Junction vertical joint
H.02	Window junction
H.03	External corner
H.04	Internal corner
V.01	Roof trim
V.02	Abutting pavement
V.03	Window header
V.04	Window-sill connection


Rockpanel A2 9 mm
PlankClip on timber. Section A-A




H.01 Junction vertical joint



H.02 Window junction




H.03 External corner




H.04 Internal corner


Rockpanel A2 9 mm
PlankClip on timber. Section B-B




V.01 Roof trim -parapet



V.03 Window header



V.02 Abutting pavement




V.04 Window-sill connection


Descriptions

1	Rockpanel A2 9 mm
2	Air cavity
3	Insulation (ROCKWOOL)
4	Timber battens
5	PlankClip (RCLIP)
6	PlankClip (RCLIP-SHORT)
7	SFS SDAW fastener 4.5 x 34 mm
8	SFS TU-S 6 x 9 mm anchor
9	Joint 6 mm
10	Cavity closure
11	Ventilation opening
12	Ventilation profile / Anti-Insect mesh
13	Windowsill with end dam
14	Metal cover/flashing
aR1	≥ 20 mm
aR2	≥ 50 mm



217d

Rockpanel A2 9 mm
PlankClip on aluminium.





A-A




B-B


Details:

H.01	Junction vertical joint
H.02	Window junction
H.03	External corner
H.04	Internal corner
V.01	Roof trim
V.02	Abutting pavement
V.03	Window header
V.04	Window-sill connection


Rockpanel A2 9 mm
PlankClip on aluminium. Section A-A




H.01 Junction vertical joint



H.02 Window junction




H.03 External corner




H.04 Internal corner


Rockpanel A2 9 mm
PlankClip on aluminium. Section B-B




V.01 Roof trim -parapet



V.03 Window header



V.02 Abutting pavement



V.04 Window-sill connection

Descriptions

1	Rockpanel A2 9 mm
2	Air cavity
3	Insulation (ROCKWOOL)
4	Aluminium rail
5	PlankClip (RClip)
6	PlankClip (RClip-SHORT)
7	SFS SDAW fastener 4.5 x 34 mm
8	SFS TU-S 6 x 9 mm anchor
9	Joint 6 mm
10	Cavity closure
11	Ventilation opening
12	Ventilation profile / Anti-Insect mesh
13	Windowsill with end dam
14	Metal cover/flashing
aR1	≥ 20 mm
aR2	≥ 50 mm

5 Planning and services

Specifications

Select the relevant specification along with the selected material to match your product finish, colour and accessory requirements. All specifications are downloadable on www.rockpanel.com.

Building Information Modelling

Building Information Modelling (BIM) is an important aspect of the planning and implementation of construction projects. In order to help with this process, the Rockpanel website provides BIM data files for the full range of our facade panels, which you can access and insert into digital building models. The BIM data files can be downloaded from the website.

CAD drawings

Rockpanel offers a wide range of CAD drawings online. The drawings are easy to download in PDF, DXF and DWG files and illustrate clearly how specific design details can be produced.

Sample request

On the Rockpanel website www.rockpanel.com/uk/ you can easily request your sample.

References

Register to receive inspiring Rockpanel case studies, product launches and other news from across the globe. Go to the “Inspiration” section on our website for more stimulating projects!

ETA and CE marking

With regard to the EOTA procedure for innovative products, Rockpanel boards have been evaluated and approved in accordance with the European Assessment Document (EAD) no. 090001-00-0404. On the basis of this guideline Rockpanel products have received a European Technical Assessment (ETA).

With regard to the ETA all products have a declaration of performance and CE marking thereby fully complying with the construction product regulations in the UK and Europe.

Guarantee

Rockpanel provides a 10-year project guarantee for our main product portfolio. For Rockpanel Premium, we extend this offering with a 15-year project guarantee. To qualify for this guarantee, it is required to register your project with us. Should you require additional information or wish to obtain the project guarantee template form, please contact our Customer Service team for assistance.

ETA

Rockpanel boards need to be applied in all according ETA. For the latest information and updates of our ETA’s please visit the Rockpanel website. Please see Rockpanel boards and corresponding ETA numbers below.

ETA-18/0883: Rockpanel Premium A2 11 mm with visible fixing


ETA-25/1032: Rockpanel Premium A2 11 mm with concealed fixing

ETA-24/0911: Rockpanel Plankclip A2 9 mm

ETA-24/0910: Rockpanel Colours, Chameleon, Metals, Stones and Woods A2 8 mm



The greatest possible care has been taken in the design and composition of this guide. Nevertheless, we cannot guarantee the completeness and correctness of the information included herein. Price and product changes are reserved. Illustrations, colours, descriptions and information relating to dimensions, characteristics etc. apply only by approximation and are not binding. All of the information in this guide is protected by copyright. This guide, the texts, photos, other information included therein and/ or parts thereof may not be reproduced, modified or published without the prior written approval of Rockpanel.



Rockpanel®

Part of ROCKWOOL Group

MADE FROM STONE

www.rockpanel.com
Learn more about us, ask for product samples and be inspired by attractive reference projects.

www.facebook.com/rockpanel
Be the first to discover our latest international projects.

www.x.com/rockpanel
Follow us for the latest news and updates.

www.linkedin.com/company/rockpanel-official
Engage and interact.

www.instagram.com/rockpanel
Get inspired.

full scope
CERTIFIED
cradle to cradle
silver version 4.0
C2CCERTIFIED.ORG

RP DG UK / 202605 / UK / Version 2.0